



25|30 litres


JERRYCAN SK96 ELECTR. CONDUCTIVE

Jerrycan SK96 electrically conductive 25|30 L


Overview

Nominal volume:	25 litres	30 litres
Item name:	KA250-SK96EX	KA300-SK96EX
Overflow volume:	29 litres	34.2 litres
Dimensions in mm:	25 litres Length = 377 Width = 240 Height = 389	30 litres Length = 377 Width = 240 Height = 457
Material and colour:	PE electr. conductive, black	
Weight:	1,250 g	1,400 g
Surface resistance (Ro):	electr. conductive $10^4 \Omega < R_o < 10^9 \Omega$	
Approval: 	according to UN approval list	
Packaging unit:	25 litres: 60 pcs. per pallet 30 litres: 50 pcs. per pallet	

Dimensions



Pallet scheme for Euro pallets (800 x 1,200 mm)



10 pcs.

Detailed view



Jerrycan w. screw cap SK96



Jerrycan w. large opening (80mm)

Advantages

- Internationally approved for active storage and transport of flammable liquids (AI/AII/AIII) acc. to class 3 of the dangerous goods transport regulations GGVs/GGVE/GGVSee and TRbF (Technical Rules for flammable liquids)
- Container made of electrically conductive, high-molecular-weight high density polyethylene (HDPE) (surface resistance $< 10^6 \text{ Ohm/Surface}$ resistivity $> 10^4$ and $< 10^9 \text{ Ohm}$), black
- Approved for use in mining acc. to DIN 22100-7
- Approval for water and 5 standard liquids
 - Wetting agent
 - Acetic acid
 - N-butyl acetate / wetting agent
 - Hydrocarbon mixture
 - Nitric acid
- Special approvals on request
- Jerrycan acc. to EN 12712-2009
- Large opening, inner $\varnothing$ 80 mm

Accessories:

- Customer-specific embossing plate on request
- Screw cap SK96, acc. to EN 12713-2009
- Filling opening SK96x8, inner diameter 80 mm, acc. to EN 12712-2009
- Degassing valve available on request
- Tamper-evident protection



FRIES Kunststofftechnik GmbH

Schützenstraße 19, 6832 Sulz, Austria

P +43 (0)5522 4935-202, F +43 (0)5522 4935-209

E info@fries.at, www.fries-kt.com



VK-SK96 11/16-V1