


FRIES




10|30|60 litres

JERRYCAN ELECTRICALLY CONDUCTIVE


Jerrycan electrically conductive 10|30|60 L

Overview			
Nominal volume:	10 litres	30 litres	60 litres
Item name:	ECO 100EX	F105EX	ECO603EX
Overflow volume:	12.7 litres	32.3 litres	62.4 litres
Dimensions in mm:	10 litres Length = 230 Width = 190 Height = 340	30 litres Length = 373 Width = 268 Height = 427	60 litres Length = 395 Width = 321 Height = 624
Material and colour:	PE electr. conductive, black		
Weight:	600 g	1,600 g	2,800 g
Surface resistance (Ro):	electr. conductive $10^4 \Omega < R_o < 10^9 \Omega$		
Approval: 	according to UN approval list		
Packaging unit:	10 litres: 80 pcs. on Euro pall. 30 litres: 45 pcs. on Euro pall. 60 litres: 28 pcs. on Euro pall.		


Dimensions




Pallet scheme for Euro pallets (800 x 1,200 mm)



10L ECOSSET




30L F105



60L triple grip

Detailed view



Guaranteed residue emptying

Advantages

- Internationally approved for active storage and transport of flammable liquids (AI/AII/AIII) acc. to class 3 of the dangerous goods transport regulations GGVS/GGVE/GGVSee and TRbF (Technical Rules for flammable goods)
- Container made of electrically conductive, high-molecular-weight high-density polyethylene (HDPE) (surface resistance $< 10^6 \text{ Ohm}$ /Surface resistivity $> 10^4$ and $< 10^9 \text{ Ohm}$), black
- Multiple use over 5 years
- Reduction of packaging waste pursuant to the packaging regulation
- Perfect residue emptying in each pouring position
- Full use of the fill goods
- Easy cleaning
- No rust
- Saves space with optimum use of the pallet
- Stackable up to a height of 3 m
- Easy disposal in line with HDPE recycling
- Screw cap with PE seal
- Special colours on request

Accessories:

- Customer-specific embossing plate on request
- Screw cap SK60 or SK70, acc. to EN 12713-2009
- Filling opening SK60x6 (inner diameter 48 mm) or SK70x6 (inner diameter 57 mm), acc. to EN 12712-2009
- Degassing valve available on request
- Tamper-evident protection